

Potência (watts)	Bulbo	Compr. (mm)	Diâm. (mm)	Base	Fluxo Lum. (lm)	Rendimento (lm/W)	Temperatura de Cor	IRC	Unid. p/cx.	Vida média (horas)
------------------	-------	-------------	------------	------	-----------------	-------------------	--------------------	-----	-------------	--------------------



BRANCA CONFORT

16	T-8	604	26	G13	1.070	67	4.000 K	65	25	7.500
32	T-8	1.214	26	G13	2.350	74	4.000 K	65	25	7.500



LUZ DO DIA PLUS

15	T-8	452	26	G13	840	56	5.200 K	72	25	7.500
15	T-12	452	38	G13	750	50	5.200 K	72	25	7.500
20	T-12	604	38	G13	1.060	53	5.200 K	72	25	7.500
30	T-8	909	26	G13	2.000	67	5.200 K	72	25	7.500
30	T-12	909	38	G13	2.100	70	5.200 K	72	25	7.500
40	T-12	1.214	38	G13	2.700	80	5.200 K	72	25	12.000
60	T-12	1.166	38	D.C.E.	3.800	63	5.200 K	72	25	12.000
65	T-12	1.500	38	G13	4.500	69	5.200 K	72	25	12.000
85	T-12	1.775	38	D.C.E.	5.700	67	5.200 K	72	15	12.000
110	T-12	2.385	38	D.C.E.	7.750	70	5.200 K	72	15	12.000



BRANCO REAL PLUS

60	T-12	1.166	38	D.C.E.	2.900	48	3.400 K	86	15	12.000
----	------	-------	----	--------	-------	----	---------	----	----	--------



DAYLIGHT

8	T-5	302	16	G5	340	43	6.500 K	65	25	6.000
18	T-8	604	26	G13	1.050	58	6.500 K	65	25	7.500
32	T-8	1.214	26	G13	2.100	66	6.500 K	65	25	7.500
36	T-8	1.214	26	G13	2.500	69	6.500 K	65	25	7.500



BRANCO LUMINOSO

20	T-12	604	38	G13	1.075	54	6.500 K	65	25	7.500
40	T-12	1.214	38	G13	2.600	65	6.500 K	65	25	12.000
110	T-12	2.385	38	D.C.E.	7.400	67	6.500 K	65	15	12.000




ALVORADA PLUS

20	T-12	604	38	G13	1.300	65	3.500 K	57	25	7.500
40	T-12	1.214	38	G13	3.200	80	3.500 K	57	25	12.000
60	T-12	1.166	38	D.C.E.	4.200	70	3.500 K	57	25	12.000
85	T-12	1.775	38	D.C.E.	6.300	74	3.500 K	57	15	12.000
110	T-12	2.385	38	D.C.E.	8.600	78	3.500 K	57	15	12.000



DESIGNER 3.000

14	T-5	563	16	G5	1.350	96	3.000 K	85	25	20.000
20	T-12	604	38	G13	1.450	72	3.000 K	85	25	7.500
28	T-5	1.163	16	G5	2.900	103	3.000 K	85	25	20.000
40	T-12	1.214	38	G13	3.700	92	3.000 K	85	25	12.000
110	T-12	2.385	38	D.C.E.	9.900	90	3.000 K	85	15	12.000



DESIGNER 4.000

14	T-5	563	16	G5	1.350	96	4.000 K	85	25	20.000
16	T-8	604	26	G13	1.200	75	4.000 K	85	25	7.500
20	T-12	604	38	G13	1.320	72	4.000 K	85	25	7.500
28	T-5	1.163	16	G5	2.900	103	4.000 K	85	25	20.000
32	T-8	1.214	26	G13	2.700	84	4.000 K	85	25	7.500
40	T-12	1.214	38	G13	3.400	85	4.000 K	85	25	12.000
54	T-5	1.163	16	G5	5.000	93	4.000 K	85	25	20.000
60	T-12	1.166	38	D.C.E.	4.180	70	4.000 K	85	15	12.000
85	T-12	1.775	38	D.C.E.	7.100	84	4.000 K	85	15	12.000
110	T-12	2.385	38	D.C.E.	9.800	89	4.000 K	85	15	12.000



DESIGNER 5.000

16	T-8	604	26	G13	1.200	75	5.000 K	85	25	7.500
20	T-12	604	38	G13	1.350	68	5.000 K	85	25	7.500
40	T-12	1.214	38	G13	3.100	78	5.000 K	85	25	12.000
85	T-12	1.775	38	D.C.E.	7.900	93	5.000 K	85	15	12.000
110	T-12	2.385	38	D.C.E.	8.900	81	5.000 K	85	15	12.000

FLUORESCENTES TUBULARES

Potência (watts)	Bulbo	Compr. (mm)	Diâm. (mm)	Base	Fluxo Lum. (lm)	Rendimento (lm/W)	Tonalidade	IRC	Unid. p/cx.	Vida média (horas)
------------------	-------	-------------	------------	------	-----------------	-------------------	------------	-----	-------------	--------------------

COLORIDA

20	T-12	604	38	G13	650	33	Azul	*	25	7.500
20	T-12	604	38	G13	930	47	Ouro	*	25	7.500
20	T-12	604	38	G13	580	29	Rosa	*	25	7.500
20	T-12	604	38	G13	1.560	78	Verde	*	25	7.500
20	T-12	604	38	G13	85	4	Vermelho	*	25	7.500
40	T-12	1.214	38	G13	1.100	28	Azul	*	25	12.000
40	T-12	1.214	38	G13	1.530	38	Ouro	*	25	12.000
40	T-12	1.214	38	G13	1.380	35	Rosa	*	25	12.000
40	T-12	1.214	38	G13	2.850	71	Verde	*	25	12.000
40	T-12	1.214	38	G13	220	6	Vermelho	*	25	12.000



GROLUX

15	T-12	452	38	G13	280	19	Grolux - 8.500 K	*	25	7.500
20	T-12	604	38	G13	370	19	Grolux - 8.500 K	*	25	7.500
30	T-12	909	38	G13	700	23	Grolux - 8.500 K	*	25	7.500
40	T-12	1.214	38	G13	950	24	Grolux - 8.500 K	*	25	12.000



AQUASTAR

15	T-8	452	26	G13	650	43	Aquastar - 10.000 K	*	25	7.500
18	T-8	604	26	G13	900	50	Aquastar - 10.000 K	*	25	7.500
30	T-8	909	26	G13	1.700	57	Aquastar - 10.000 K	*	25	7.500



DAYLIGHTSTAR

15	T-8	452	26	G13	900	60	Daylightstar - 5.000 K	*	10	7.500
18	T-8	604	26	G13	1.300	72	Daylightstar - 5.000 K	*	10	7.500
30	T-8	909	26	G13	2.350	78	Daylightstar - 5.000 K	*	10	7.500



CORALSTAR

18	T-8	604	26	G13	*	*	Coralstar - Actínica	*	10	7.500
30	T-8	909	26	G13	*	*	Coralstar - Actínica	*	10	7.500



REPTISTAR TERRARIUMS

15	T-8	452	26	G13	300	20	Reptistar - 6.500 K	*	10	7.500
30	T-8	909	26	G13	700	23	Reptistar - 6.500 K	*	10	7.500



ACTIVA

36	T-8	1.214	26	G13	2.300	64	Activa - 6.500 K	98	25	7.500
----	-----	-------	----	-----	-------	----	------------------	----	----	-------



LUZ NEGRA

8	T-5	302	16	G5	*	*	Black Light 350	*	25	6.000
15	T-8	452	26	G13	*	*	Black Light 350	*	25	7.500
15	T-12	452	38	G13	*	*	Black Light 350	*	25	7.500
20	T-12	604	38	G13	*	*	Black Light 350	*	25	7.500
30	T-12	909	38	G13	*	*	Black Light 350	*	25	7.500
40	T-12	1.214	38	G13	*	*	Black Light 350	*	25	12.000



* Não aplicável
G13 = Bipino
D.C.E. = Duplo Contato Embutido

SÃO PAULO - FÁBRICA E ESCRITÓRIO
Rua Amoipirá, 81 - Sto. Amaro CEP 04689-900
Centro Sylvania de Informação ao Consumidor:
Tel: (11) 5633-2430 Fax: (11) 5631-9776
e-mail: sac@sylvania.com.br

REGIONAIS DE VENDAS:
BELO HORIZONTE MG Tel.: (31) 3224-4677 Fax: (31) 3224-4937
PORTO ALEGRE RS Tel.: (51) 3337-7939 Fax: (51) 3337-5260
RIO DE JANEIRO RJ Tel.: (21) 2265-2585 Fax: (21) 2556-2068